AQUA FIGHTER

ELASTOMERIC ROOF KOTE - FIBER TECH

PRODUCT DESCRIPTION

Aqua Fighter, Elastomeric Roof Kote – Fiber Tech is a high-performance, fiber-reinforced elastomeric coating specially developed for roof waterproofing and protection. Formulated with resilient acrylic polymers and reinforcing synthetic fibers, it creates a flexible, seamless and durable protective layer after curing. The coating helps prevent water penetration while providing long-lasting resistance against rain, moisture and challenging weather conditions.

KEY FEATURE

Fiber-Reinforced Strength
Reinforced with synthetic fibers for improved durability and added film strength.

Superior Waterproofing
Forms a seamless protective barrier that helps prevent water penetration.

UV & Weather Resistance
Helps protect the roof surface against UV exposure and harsh weather conditions.

High Elongation & Crack Bridging
Flexible elastomeric film helps bridge hairline cracks and minor surface movement.

Strong Concrete Adhesion
Provides strong bonding to properly prepared concrete and masonry surfaces.

Reduces Roof Temperature
Reflective properties help reduce heat build-up on exposed roof surfaces.

AREAS OF APPLICATION



Building Roofs & Terraces



Sunshades & Exterior Vertical Walls



Brick Bat Coba

AQUA FIGHTER

ELASTOMERIC ROOF KOTE – FIBER TECH

TECHNICAL PROPERTIES

Property	Test Method	Results
Color	Visual	White, Grey, Marine Red, Tennis Green etc.
pH	-	9-10
Viscosity	ASTM D562	125±5 KU
Water Absorption (48 hr.)	ASTM D6489	0.49%
Adhesion Strength	ASTM C633	3.7 MPa
Percent Elongation	ASTM D638	390%
Solar Reflection Index	ASTM E1980	98.02

SURFACE PREPARATION



Clean surface
(dust, grease, loose particles)



Remove old coatings completely



Repair cracks & damaged areas

APPLICATION PROCESS

1st Coat

Roof Kote Paint Diluted with 30% Water

2nd Coat

Apply Roof Kote paint Directly [Horizontally]

3rd Coat

Apply Roof Kote paint Directly [Vertically]

Recoating Time: 4-6 hours

AQUA FIGHTER

ELASTOMERIC ROOF KOTE - FIBER TECH

PACK SIZE

3.64 Liters | 18.2 Liters

STORAGE & SHELF LIFE

Shelf life: 12 months. Store in a cool & dry place

SAFETY PRECAUTIONS

Avoid contact with eyes/skin. Use gloves during application. Do not apply during rain.



DISCLAIMER

Vales are based on laboratory tests. Actual performance may vary depending surface condition and application method.