AQUA INTERIOR SEALER

aqua paints
দেশের রঙে রাঙাই দেশ

PRODUCT DESCRIPTION



Aqua Interior Sealer is made with special quality styrene acrylic emulsion and inert extenders. It is water-resistant and suitable for use in all types of plastered walls, cement surfaces, and as a primer/sealer in concrete surface, masonry surfaces, asbestos, hard & soft boards etc.

- LEAD FREE
- FAST DRY
- HIGH QUALITY PURE BINDER
- EXCELLENT ADHESION

PRODUCT INFORMATION

Pack Size



Coverage

FOR INTERIOR
180-200 SFT/Ltr/1 Coat

*Depending on Surface



SURFACES

- Interior Plaster
- Masonry
- Asbestos
- Concrete
- Hard & Soft Boards

METHOD OF APPLICATION

1. Clean the surface with a wire brush, wash, and dry completely.
2. Apply 1 coat of 100% thinned Aqua Interior Sealer and dry for 10–12 hours.
3. Apply 2 coats of Aqua Joy Putty at 6–8 hour intervals.
4. Apply 1 coat again of 100% thinned Aqua Interior Sealer and dry for 10–12 hours.

AQUA INTERIOR SEALER

aqua paints
দেশের রঙে রাঙাই দেশ

MIXING RATIOS

For Interior
Sealer : Water = 1:1

SHADES

White

PRODUCT SPECIFICATION

Pigments	Titanium Dioxide & Alkali Resistance Extenders
Thinner	Clean Water
pH	8.5 - 9.0
Touch Dry	30 Minutes
Hard Dry	10-12 Hours (Recoat)
Viscosity	110±5 KU @30°C
Binder	Special Quality Styrene Acrylic Emulsion
Finish	Matt
Heavy Metal Content	Not Detected
Application Method	Brush, Roller
Pot Life after Thinning	12 Hours Maximum
Storage	12 months in a sealed container stored in a cool & dry place

CERTIFIED ISO 9001:2015 COMPANY