AQUASEAL

Damp Proof Sealer

aqua paints
দেশের রঙে রাঙাই দেশ

PRODUCT DESCRIPTION



Aquaseal is a premium quality sealer formulated with special Acrylic Emulsion binder to provide excellent adhesion and deep penetration into wall surfaces. Its fine-grade fillers effectively seal surface porosity, creating a smooth and uniform base for the application of the finish coat.

With excellent resistance to alkali and efflorescence, Aquaseal forms a protective film that helps block the passage of salts and alkaline substances through the wall, thereby enhancing surface protection and supporting better, longer-lasting paint performance.

- LEAD FREE
- EXCELLENT ADHESION
- EXCELLENT WATER RESISTANCE
- EXCELLENT ALKALI RESISTANCE

PRODUCT INFORMATION

Pack Size



0.90 Liter | 3.60 Liters | 18 Liters

Coverage

FOR INTERIOR
60-70 SFT/Ltr/2 Coats

FOR EXTERIOR
30-35 SFT/Ltr/2 Coats

*Depending on Substrate Condition



SURFACES

- Interior/Exterior Plaster
- Masonry
- Asbestos
- Concrete
- Hard & Soft Boards

METHOD OF APPLICATION

1. Remove dust, grease, oil, mildew, and other contaminants.
2. Fill holes, cracks, and seal joints properly.
3. Scrape off all loose, peeling, or poorly adhered paint.
4. Apply 2 coats of Aquaseal Sealer evenly over the prepared surface and allow it to dry properly.

AQUASEAL
Damp Proof Sealer

aqua paints
দেশের রঙে রাঙাই দেশ

MIXING RATIOS

For Interior
Sealer : Water = 2:1

For Exterior
Sealer : Water = 7:1

SHADES

White

PRODUCT SPECIFICATION

Pigments	Titanium Dioxide & Alkali Resistance Extenders
Thinner	Clean Water
pH	8.5 - 9.0
Touch Dry	40 Minutes
Hard Dry	5-6 Hours (Recoat)
Viscosity	110±5 KU @30°C
Binder	Special Acrylic Emulsion
Finish	Matt
Heavy Metal Content	Not Detected
Storage	12 months in a sealed container stored in a cool & dry place

CERTIFIED ISO 9001:2015 COMPANY